



Our Altair overhead lift is a lightweight portable lift with a discreet and modern design. Its portability ensures greatly reduced asset investments as the same lift can be used in multiple rooms. The lift is available in three weight capacities.

Unbeatable Comfort

When used with our sling range, the Altair offers unbeatable user comfort. The hanger bar is available in two different sizes with a quick release install that makes it convenient to use for many different users and needs. With weight capacities of 150kg, 200kg and 300kg, the Altair is the optimal solution for facilities that need a versatile lifting solution.

Lift Intelligence

The Altair features an advanced technology platform that allows tracking of lift usage and visualization of collected data. This integrated lift intelligence allows data to be retrieved using our Data and Service Application on a tablet or computer. Detailed

information can be viewed directly in the application or exported to other media for additional analysis.

Optimal Features

The Altair features an easy to use handset as well as a secondary control panel right on the lift. The 3-point suspension offers an even weight distribution and elongated sitting position. The soft-start, soft-stop and constant lifting speed and direction makes lifting a comfortable experience for patients regardless of their weight. The Altair offers two-speed lifting, high battery capacity and convenient battery charging through the hand control.

HUMAN CARE SWEDEN (HQ)

Årstaängsvägen 21B
117 43 Stockholm
Phone:- +46 8 665 35 00
Fax:- +46 8 665 35 10
info.se@humancaregroup.com

HUMAN CARE CANADA

10-155 Colonnade Road
Ottawa, ON K2E 7K1
Phone: +613.723.6734
Fax: +613.723.1058
info.ca@humancaregroup.com

HUMAN CARE NEDERLAND

Elspeterweg 124
8076 PA Vierhouten
Phone: +31 577 412 171
Fax: +31 577 412 170
info.nl@humancaregroup.com

HUMAN CARE UNITED STATES

8006 Cameron Road, Suite K
Austin, TX 78754
Phone: +512.476.7199
Fax: +512.476.7190
info.us@humancaregroup.com

Accessories



Hanger bar

Quick release for optimal convenience. Order separately. Part no.: 55751 (45cm/17.7") 55764 (55cm/21.7")



Basic Sling

The Basic sling is a comfortable sling without reinforcements, handles, or padding. See our entire Sling portfolio on our website.



Hand control

Two speed with up/down mode. Input for charging and USB interface. IPX7 water protection rating. Part no.: 71457



Upholstered Cover

Protects user from hanger bar impact. Hanger bar sold separately. Part no. 50866



Lift charger

Charger with holder. Easily attaches to wall. Part no. 50899-US



Secondary Control

Secondary control panel on back of lift for emergency stop function. Integrated feature.



4-point suspension

Enables 4-point lifting. Placed on leg hook. Part no.: 55619



Distance Strap

Reinforced nylon thread and metal hooks. Extend lift strap up to 100cm/39.3". Part no. 20124-xx (specify length)



Insights

Lift intelligence that facilitates cloud based storage of collected data. Integrated feature.



Lift Trolley

Simplifies transport of lift between rooms. Convenient sling storage. Part no.: 70346



Scale

Medical grade scale. Max. capacity 320kg/705.5lb. ISO and EN compliant. Art. no: 50590 (RoomerS & Altair) 50591 (Heliq)

*Spreader Bar Small: 92441 is manual.

Technical Specifications

Description	Altair 150	Altair 220	Altair 300
Part Number (Lift)	55200H-[Country Code*]	55210H-[Country Code*]	55220H-[Country Code*]
Part Number (Hanger Bar)	55751 (45cm/17.7") or 55764 (55cm/21.7")	55751 (45cm/17.7") or 55764 (55cm/21.7")	55751 (45cm/17.7") or 55764 (55cm/21.7")
Dimensions (W x H x L)	23,5cm x 14cm x 30cm 9.2" x 5.5" x 11.8"		
Safe Working Load	150kg/330lb	220kg/484lb	300kg/661lb
Product Weight (Lift)	7.4kg / 16.2lb		
Product Weight (Hanger Bar)	1.3kg/2.8lb (55751) or 1.5kg/3.3lb (55764)		
Battery	2.3Ah, 2x12V		
Battery Charger	Input: 100-240V, AC 50-60 Hz Output: 27.8V, 0.8A DC		
IP Class	Lift: IPX4 Hand Control: IPX7		
Lifting Distance and Speed	Distance: 212 cm / 83.5" Speed: 1.8m/min - 3 m/min — 70"/min - 118"/min		
Approvals	ROHS-2 approved, Tested and approved according to ISO 10535:2006 ETL Listed		
Emergency Lowering	Electronic and Mechanical		

*Country Codes: AU-Australia, GB-Great Britain, EU-Europe, JP-Japan, NA-North America



We improve freedom of movement
and quality of care for people.